



HD / 1,280 x 720 H.264 Wireless Network Camera (BL-VP104W)
HD / 1,280 x 720 H.264 Network Camera (BL-VP104)

Key Features

- 720p HD images up to 30 fps
- 1.0 Megapixel high sensitivity CMOS Sensor
- Multiple H.264 (High profile) streams and JPEG streams ensure simultaneous real time monitoring and high resolution recording by “UniPhier®”, Panasonic’s proprietary System LSI platform.
- Full frame (Up to 30 fps) transmission at 1,280 x 720 image size
- High sensitivity with Day & Night (Electrical) function: 0.9 lx (Color), 0.6 lx (B/W) at F2.8
- Digital Noise Reduction: 3D-DNR ensures noise reduction in various conditions.
- Progressive scan ensures clear images with less motion blur and no tearing even when the subject is moving.
- Electronic sensitivity enhancement: Auto (Up to 16x) / OFF
- Selectable light control modes: Indoor scene (50 Hz) / Indoor scene (60 Hz) / ELC (maximum exposure time)
Indoor scene (50 Hz/60Hz): Flicker caused by fluorescent lightning will be automatically compensated.
ELC (maximum exposure time): The lightning control will be automatically performed by adjusting shutter speed in the range of ELC.
- 1.5x extra zoom under VGA resolution
- 4x digital zoom controlled by browser
- VMD (Video Motion Detection) with 4 programmable detection areas, 15 steps sensitivity level and 10 steps detection size
- Face detection function detects the position of human face and the information is sent by XML or video stream.
- Privacy Zone can mask up to 2 private areas, such as house windows and entrances/exits.
- Camera title display: Up to 20 alphanumeric characters on the browser
- Alarm sources including VMD and Panasonic alarm command can trigger actions such as FTP image transfer, E-mail notification, Indication on browser, and Panasonic alarm protocol output.
- JPEG Image compression ratio can be changed by alarm so that higher quality image can be provided.
- Prioritized stream control: One of the video streams can be prioritized when multiple recorders or client PCs are accessing the camera so that the recorder or the client PC can maintain the frame rate.
- H.264 max. bit rate/client and Total bit rate control allows flexible network traffic management. Frame rate priority mode controls bit rate and compression ratio to provide the specified frame rate.

- Internet mode: H.264 images can be transmitted over HTTP protocol.
- Multi-language: English / Italian / French / German / Spanish / Russian / Chinese / Japanese
- IPv4/IPv6 protocol supported
- Supports SSL, DDNS (viewnetcam, RFC2136)
- Still images (JPEG) can be viewed on mobile phones via Internet.
- Onvif compliant model
- Smartphone monitoring : Direct camera control from smartphone
- Wireless LAN function (IEEE802.11 n/b/g) : Camera images can be monitored over a wireless router. (BL-VP104W)
- WPS (Wi-Fi Protected Setup) function : WPS enables the camera to automatically obtain the connection configuration information and the security configuration information of the wireless router. WPS can be configured by pressing the WIRELESS button (WPS indicator) (PBC method) or entering an 8 digit pin code (Pin code method). (BL-VP104W)
- PC software recording (BB-HNP17: Network Camera Recorder with Viewer Software)

Standard Accessories

- | | | | |
|--|-------|-----------------------------|-------|
| • Flexible Stand | 1 pc. | • Installation Guide | 1 pc. |
| • AC Adaptor | 1 pc. | • CD-ROM ¹ | 1 pc. |
| • Configure the settings of the camera | 1 pc. | | |

¹The CD-ROM contains the operating instructions and different kinds of tool software programs.


Specifications

	BL-VP104W	BL-VP104		
Camera	Image Sensor	1/4 type CMOS Sensor		
	Effective Pixels	Approx. 1 megapixel		
	Scanning Mode	Progressive		
	Scanning Area	3.89 mm (H) x 2.43 mm (V) {5/32 inches (H) x 3/32 inches (V)}		
	Minimum Illumination	Color: 0.9 lx (F2.8, Auto slow shutter: Off (1/30s), Gain:On(High)) ¹		
		Color: 0.06 lx (F2.8, Auto slow shutter: Max. 16/30s, Gain:On(High)) ¹		
		BW: 0.6 lx (F2.8, Auto slow shutter: Off (1/30s), Gain:On(High)) BW: 0.04 lx (F2.8, Auto slow shutter: Off (16/30s), Gain:On(High)) ¹		
	White Balance	AWC (2,000 ~ 10,000 K), ATW1 (2,700 ~ 6,000 K), ATW2 (2,000 ~ 6,000 K)		
	Light Control Mode	Indoor scene (50 Hz / 60 Hz) / ELC		
	Shutter Speed	ELC (1/30 s), ELC (3/100 s), ELC (3/120 s), ELC (2/100 s), ELC (2/120 s), ELC (1/100 s), ELC (1/120 s), ELC (1/250 s), ELC (1/500 s), ELC (1/1,000 s), ELC (1/2,000 s), ELC (1/4,000 s), ELC (1/10,000 s)		
	Adaptive Black Stretch	ON / OFF		
	AGC	ON (HIGH) / ON (MID) / ON (LOW) / OFF		
	Electronic Sensitivity UP Day & Night (electrical)	OFF (1/30 s), Max. 2/30 s, Max. 4/30 s, Max. 6/30 s, Max. 10/30 s, Max. 16/30 s		
	Digital Noise Reduction	OFF / AUTO		
	Video Motion Detection	HIGH / LOW		
Privacy Zone	ON / OFF (4 areas available)			
Camera Title (OSD)	ON / OFF (up to 2 zones available)			
Camera Title (OSD)	Up to 20 characters (alphanumeric characters, marks), On/Off			
Wireless (BL-VP104W/ BL-VP104WE/ BL-VP104WU only)	Focal Length	3.6 mm		
	Zoom Ratio	Extra zoom: 1.5x (at VGA resolution)		
	Angular Field of View	Horizontal: 57°, Vertical: 34°		
	Maximum Aperture Ratio	1 : 2.8		
	Focusing Range	0.4 m ~ ∞		
	Antenna	1x1 (Diversity)		
	Transmission method	SISO (Single Input/ Single Output) -OFDM, OFDM, DSSS		
	Frequency range (center frequency)/ Channel	BL-VP104W: 2.412 GHz - 2.462 GHz (1 - 11ch) BL-VP104WE: 2.412 GHz - 2.472 GHz (1 - 13ch) BL-VP104WU: 2.412 GHz - 2.472 GHz (1 - 13ch)		
	Data transfer rate: ²	IEEE802.11n: 6.5 - 72.2 Mbps IEEE802.11g: 6 - 54 Mbps IEEE802.11b: 1 - 11 Mbps		
	Access method	Infrastructure mode		
Authentication method	Open System			
Security: ³	WPA/WPA2-PSK (TKIP/AES) WEP (64 bit/128 bit)			
WPS	PBC method (push button method), PIN method (PIN code method)			
Browser GUI	Camera Control	Brightness		
	Display Mode	Spot, Quad: Image from 16 cameras can be displayed in 4 different Quad screens or 16 split screen (JPEG only). 20 characters camera title available.		
	Zoom	extra zoom(1x - 1.5x) and the electronic zoom (higher zoom factors, up to 6x).		
	Camera Title	Up to 20 alphanumeric characters		
	Clock Display	Time: 12H/24H, Date: 5 formats on the browser, Summer time (Manual)		
	Alarm Control	Reset		
	One Shot Capture	A still picture will be displayed on a newly opened window.		
	GUI/Setup Menu Language	English, Italian, French, German, Spanish, Russian, Chinese, Japanese		
	System Log	Up to 100 (Internal), error logs		
	Supported OS: ^{4,5}	Microsoft® Windows® 7, Microsoft® Windows Vista®, Microsoft® Windows® XP SP3		
Supported Browser	Windows® Internet Explorer® 9.0 (32 bit), Windows® Internet Explorer® 8.0 (32 bit), Windows® Internet Explorer® 7.0 (32 bit), Microsoft® Internet Explorer® 6.0 SP3			
Network	Network IF	10Base-T / 100Base-TX, RJ-45 connector (female)		
	Image Resolution ⁶	Aspect ratio:	H.264: SVGA(800 x 600) / VGA (640 x 480) / QVGA (320 x 240), up to 30 fps	
		[4 : 3]	JPEG: SVGA(800 x 600) / VGA (640 x 480) / QVGA (320 x 240), up to 30 fps	
	Aspect ratio:	[16 : 9]	H.264: 1,280 x 720 / 640 x 360 / 320 x 180, up to 30 fps	
		[16 : 9]	JPEG: 1,280 x 720 / 640 x 360 / 320 x 180, up to 30 fps	
	H.264	Transmission Mode	Constant bitrate / Frame rate / Best effort	
		Frame Rate	1 / 3 / 5 / 7.5 / 10 / 12 / 15 / 20 / 30 fps	
		Bit Rate/Client	64 / 128 / 256 / 384 / 512 / 768 / 1,024 / 1,536 / 2,048 / 3,072 / 4,096 / 8,192 kbps	
	Image Quality	Refresh Interval	LOW / NORMAL / FINE	
		Transmission Type	1 fps ~ 30 fps	
		Transmission Type	UNICAST / MULTICAST	
	JPEG	Image Quality	10 steps	
		Refresh Interval	0.1 fps ~ 30 fps	
		Transmission Type	PULL / PUSH	
	Supported Protocol	IPv6: TCP/IP, UDP/IP, HTTP, HTTPS, RTP, FTP, SMTP, DNS, NTP, SNMP, DHCPv6, MLD, ICMP, ARP IPv4: TCP/IP, UDP/IP, HTTP, HTTPS, RTSP, RTP, RTP/RTCP, FTP, SMTP, DHCP, DNS, DDNS, NTP, SNMP, UPnP, IGMP, ICMP, ARP		
FTP Client	Alarm image transmission, FTP periodic transmission			
No. of Simultaneous Users	Up to 14 users (Depends on network conditions)			
Face Detection	ON / OFF (with XML notification)			
Cellular Phone Compatibility	JPEG image			
Mobile Terminal Compatibility ⁷	iPad, iPhone, iPod touch (iOS 4.2.1 or later), Android™ mobile terminals			
Alarm	Alarm Source	VMD, Command alarm		
	Alarm Actions	E-mail notification, Indication on browser, FTP image transfer, Panasonic protocol output		
	Schedule	VMD		


	BL-VP104W	BL-VP104	
General	Safety/ EMC Standard	BL-VP104W: <Safety> UL60950-1 Ed.2, C22.2 NO.60950-1 Ed.2 <EMC> FCC Part15 ClassB <Wireless> FCC Part15C BL-VP104WE / BL-VP104WU: <Safety> IEC60950-1 Ed.2 <EMC> EN55022 ClassB, EN55024 <Wireless> EN300 328	BL-VP104: <Safety> UL60950-1 Ed.2, C22.2 NO.60950-1 Ed.2 <EMC> FCC Part15 ClassB, ICES-003 ClassB BL-VP104E / BL-VP104U: <Safety> IEC60950-1 Ed.2 <EMC> EN55022 ClassB, EN55024
	Power Source and Power Consumption	6.5 V DC (Use only with Panasonic AC adapter) BL-VP104W: max. 3.5W (120 V AC/ 60 Hz) BL-VP104WE: max. 3.5 W (230 V AC/ 50 Hz) BL-VP104WU: max. 3.5 W (230 V AC/ 50 Hz)	6.5 V DC (Use only with Panasonic AC adapter) BL-VP104: max. 2.0W (120 V AC/ 60 Hz) BL-VP104E: max. 2.0 W (230 V AC/ 50 Hz) BL-VP104U: max. 2.0 W (230 V AC/ 50 Hz)
Ambient Operating Temperature	0 °C ~ 40 °C (32 °F ~ 104 °F)		
Ambient Operating Humidity	Less than 90 % (no condensation)		
Dimensions	70 mm (W) x 70 mm (H) x 25.4 mm (D) (2-3/4 inches (W) x 2-3/4 inches (H) x 1 inch (D)) (excluding projection)		
Mass (approx.)	Approx. 80 g (0.18 lbs)	Approx. 75 g (0.17 lbs)	
Finish	Main body: ABS resin, white		

- *1 Converted value
- *2 The actual line speed may be different depending on the network environment and the wireless devices connected.
- *3 Depending on the wireless router (wireless access point) used, connections may not possible between the camera and the wireless router.
- *4 When connecting with 802.11n, select WPA-PSK (AES) or WPA2-PSK (AES) for security.
- *5 Refer to "Notes on Windows Vista® / Windows® 7" on the provided CD-ROM for further information about system requirements for a PC and precautions when using Microsoft® Windows® 7 or Microsoft® Windows Vista®.
- *6 When using IPv6 for communication, use Microsoft® Windows® 7 or Microsoft® Windows Vista®.
- *7 For further information about compatible devices, refer to our website (<http://panasonic.net/pss/security/support/info.html>).

Part Names and Functions



Appearance



Trademarks and registered trademarks

- Microsoft, and Windows are registered trademarks of Microsoft Corporation in the U.S. and other countries.
- iPad, iPhone and iPod touch are registered trademarks of Apple Inc.
- UniPhier is a registered trademark of Panasonic Corporation.
- "Super Dynamic", "SDII", "SDIII", "SD5", "SD6", "SD5Link" logos are trademarks or registered trademarks of Panasonic Corporation.
- ONVIF and the ONVIF logo are trademarks of ONVIF Inc.

Important

- Safety Precaution: carefully read the operating instructions and installation manual before using this product.
- Panasonic can not be responsible for network performance and/or other manufacturer products that reside on the network.

- Masses and dimensions are approximate.
- Specifications are subject to change without notice.
- These products may be subject to export control regulations.

DISTRIBUTED BY:

Panasonic®

<http://panasonic.net/security/>

Printed in Japan (2A-095L)