




Lampada da tavolo, terra o parete/soffitto costituita da estruso in alluminio per la struttura e pressofusione di alluminio per la testa e lo snodo. Diffusore in policarbonato con perimetro luminescente e doppia serigrafia appositamente studiata per ottimizzare il fascio luminoso e ridurre l'abbagliamento. Fascio luminoso orientabile ottenuto da 1 modulo LED composto da 18 diodi. Potenza apparecchio da 8,5W (702 lm) fino a 10W (526 lm). Luce dimmerabile con CRI≥90 per tutte le versioni (tranne versione P/B) con tecnologia STEP DIM a 5 regolazioni di intensità luminosa e luce di cortesia. Struttura rifinita con vernice poliacrilica in bianco, rosso, nero, spazzolato e verniciato colore titanio, spazzolato e verniciato colore oro satinato. Testa rotante su 2 assi grazie a un doppio snodo. Miniaturizzazione del giunto a snodo con possibilità di regolarne la tenuta.

Disponibili accessori nella versione C: morsetto, perno e braccio parete. Ideale per uffici, scrivanie, studi, zone notte.


Table, floor or wall/ceiling lamp made of extruded aluminium for the structure and die-cast aluminium for the head and the junction. Diffuser in polycarbonate with luminous perimeter and double screen serigraphy, specifically designed to optimize the beam and reduce the glare. Swiveling light beam created by 1 LED module consisting of 18 diodes. Luminaire power from 8.5W (702 lm) to 10W (526 lm). Dimmable light with CRI≥90 for all versions (except for version P/B) with technology STEP DIM with 5 intensity of light settings and courtesy light. Structure in white, red, black polyacrylic paint, or brushed and colored titanium and brushed and colored satin gold. Rotating head on 2-axis through a double joint. Miniaturization of the junction with the possibility of regulating the tightness. Accessories available in the C version: clamp, pin and the wall arm. Ideal for offices, desks, studios, night zones.

PAGE CATALOGUE 88	CODICE CODE	FONTI LUMINOSE LIGHT SOURCES	Kgn
-------------------	-------------	------------------------------	-----

Tavolo / Table



59
23 1/4"



CM07701.000.0409

Potenza assorbita apparecchio / Luminaire power consumption 10W

4,20

CM07702.000.0409

Flusso luminoso apparecchio / Luminaire luminous flux 526 lm

3000K Ra 90 220-240V STEP DIM

CM07703.000.0409

CM07719.000.0409

CM07730.000.0409

AS AWARDED BY
THE CHICAGO
ATHENAEUM:
MUSEUM OF
ARCHITECTURE
AND DESIGN.




GERMAN
DESIGN
AWARD
SPECIAL
2016



DESIGN
AWARD
2016

Finalista Delta
Premios ADI
2016

Tavolo morsetto / Table clamp



59
23 1/4"



CM07701.000.0409

Potenza assorbita apparecchio / Luminaire power consumption 10W

0,80

CM07702.000.0409


Flusso luminoso apparecchio / Luminaire luminous flux 526 lm

3000K Ra 90 220-240V STEP DIM



CM07703.000.0409

CM07730.000.0409

Tavolo perno / Table pin



59
23 1/4"



CP07701.000.0409

Potenza assorbita apparecchio / Luminaire power consumption 10W

0,60

CP07702.000.0409

Flusso luminoso apparecchio / Luminaire luminous flux 526 lm

3000K Ra 90 220-240V STEP DIM

CP07703.000.0409

CP07730.000.0409

	CODICE CODE	FONTI LUMINOSE LIGHT SOURCES	Kgn
Braccio parete / Wall bracket 	CA07701.000.0409	Potenza assorbita apparecchio / Luminaire power consumption 10W	0,90
	CA07702.000.0409	Flusso luminoso apparecchio / Luminaire luminous flux 526 lm 3000K Ra 90 220-240V STEP DIM	
	CA07703.000.0409		
	CA07730.000.0409		
Terra / Floor 	T07701.000.0409	Potenza assorbita apparecchio / Luminaire power consumption 10W	4,85
	T07702.000.0409	Flusso luminoso apparecchio / Luminaire luminous flux 526 lm 3000K Ra 90 220-240V STEP DIM	
	T07703.000.0409		
	T07730.000.0409		
Faretto parete / Wall spot 	A07701.000.0409	Potenza assorbita apparecchio / Luminaire power consumption 10W	0,35
	A07702.000.0409	Flusso luminoso apparecchio / Luminaire luminous flux 526 lm 3000K Ra 90 220-240V STEP DIM	
	A07703.000.0409		
	A07730.000.0409		
Faretto parete-soffitto / Wall/ceiling spot 	P07701.000.0101	Potenza assorbita apparecchio / Luminaire power consumption 8,5W	0,35
	P07702.000.0101	Flusso luminoso apparecchio / Luminaire luminous flux 702 lm 3000K Ra 80 220-240V	
	P07703.000.0101		
	P07730.000.0101		
Led Spotlight per binario / Spotlight for electrified track 	B07701.000.0101	Potenza assorbita apparecchio / Luminaire power consumption 8,5W	0,40
	B07702.000.0101	Flusso luminoso apparecchio / Luminaire luminous flux 702 lm 3000K Ra 80 220-240V	
	B07703.000.0101		
	B07730.000.0101		

Fotometrie e Classi Energetiche disponibili www.panzeri.it / Photometric data and Energy Label available at www.panzeri.it

CODICI COLORI DISPONIBILI / COLOUR CODES AVAILABLE

01 Bianco
White

02 Nero
Black

03 Rosso
Red

30 Titanio
Titanium

19 Oro satinato solo per
versione tavolo
Satin gold table lamp

Limited edition
PANZERI
WE MAKE LIGHT

PANZERI
WE MAKE LIGHT